

TAMPER EVIDENT –A5010 - HG65

FACE MATERIAL

White matt filled expanded, highly cavitated HDPE film with special matt clay coated on one side. Low internal cohesive strength.

Typical technical values

Basis Weight	60	g/m ²	ISO 536
Caliper	109	μ	ISO 534
Opacity	92	%	DIN53146

ADHESIVE

General-purpose strong water-based acrylic adhesive.

Typical technical values

Initial Tack (on glass)	8,6 N/ Foil Tear	FINAT FTM 9
Adhesion 180° (on glass)	8,5 N/ Foil Tear	FINAT FTM 1
Application temperature min.	min.+5 °C	
Service temperature	-40 °C - +70 °C	

Preliminary tests are recommended due to different substrates and applications.

BACKING

Yellow, wood-free transparent glassine backing paper. One side siliconised.

Typical technical values

Basis Weight	57	g/m ²	ISO 536
Caliper	49	μ	ISO 534
Tensile strength MD	≥5,0	kN/m	ISO 1924
Tensile strength CD	≥2,6	kN/m	ISO 1924

Printability

This face material has a matt top coating layer. Print recommendation: thermal transfer, industrial ink jet, hot foil. However, exact ink and foil system should be recommended by your ink supplier.

Shelf life

2 years

Storage

23±2 °C, 50±5 % RH

Warranty: All statements and recommendations about BUDAVAL products are based on our most up-to-date knowledge, experience and tests believed to be reliable but do not constitute a guarantee or warranty. As the products are used outside our control we cannot take responsibility for any damage which may be caused when using the product. This technical information sheet replaces all earlier ones. All information subject to change without notice. 09/2019.