

PET WHITE MATT TC50 –A6020 - WG65

FACE MATERIAL

White top coated, matt polyester film.

Typical technical values

Basis Weight	72	g/m ²	ISO 536
Caliper	54	μ	ISO 534
Tensile Strength CD	17	Kg/mm ²	ASTM D882

ADHESIVE

Typical technical values

Initial Tack (on glass)	6 N	FINAT FTM 9
Adhesion 180° (on glass)	6 N	FINAT FTM 1
Application temperature min.	+5 °C	
Service temperature	-20 °C - +70 °C	

BACKING

White, wood-free, transparent glassine backing paper. One side siliconised.

Typical technical values

Basis Weight	58	g/m ²	ISO 536
Caliper	49	μ	ISO 534
Tensile strength MD	≥5,1	kN/m	ISO 1924
Tensile strength CD	≥2,1	kN/m	ISO 1924

Adhesive performance

This adhesive is characterized by good initial tack and adhesion. Not suitable for labelling rough surfaces plasticised PVC surfaces, greasy surfaces.

Printability

This face material has a matt top coating layer, which gives good printing performance across a wide variety of all conventional printing processes. However, exact ink and foil system should be recommended by your ink supplier.

Shelf life

2 years

Storage

23±2 °C, 50±5 % RH